

- 9. Discussion regarding title 37 TAC, Chapter 435, Firefighter Safety, including, but not limited to; §435.1 Protective Clothing and §435.19 Enforcement of Commission Rules, to include the Commission's findings on helmet damage discovered during inspections and departments duty to comply with applicable provisions of NFPA 1851.**

## Chapter 435

### FIRE FIGHTER SAFETY

#### §435.1. Protective Clothing.

(a) A regulated fire department shall:

(1) purchase, provide, and maintain a complete set of protective clothing for all fire protection personnel who would be exposed to hazardous conditions from fire or other emergencies or where the potential for such exposure exists. A complete set of protective clothing shall consist of garments including bunker coats, bunker pants, boots, gloves, helmets, and protective hoods, worn by fire protection personnel in the course of performing fire-fighting operations;

(2) ensure that all protective clothing which are used by fire protection personnel assigned to fire suppression duties comply with the minimum standards of the National Fire Protection Association suitable for the tasks the individual is expected to perform. The National Fire Protection Association standard applicable to protective clothing is the standard in effect at the time the entity contracts for new, rebuilt, or used protective clothing; and

(3) maintain and provide upon request by the Commission, a departmental standard operating procedure regarding the use, selection, care, and maintenance of protective clothing which complies with NFPA 1851, Standard on Selection, Care, and Maintenance of Structural Fire Fighting Protective Ensembles.

(b) An entity may continue to use protective clothing in use or contracted for before a change in the National Fire Protection Association standard, unless the Commission determines that the protective clothing constitutes an undue risk to the wearer, in which case the Commission shall order that the use be discontinued and shall set an appropriate date for compliance with the revised standard.

(c) Protective clothing in use or contracted for prior to January 1, 2002, shall be exempted from the record keeping requirements contained in Section 2.3, Records, of NFPA 1851.

~~[(d) — In accordance with §419.043, Texas Government Code and subsection (b) of this section as set out hereinabove and consistent with past practice with respect to the implementation of NFPA standards when immediate implementation of a standard as written is impractical for Texas, the modifications contained in Sections 10.1.2, 10.1.3, and 10.1.3.1 of the 2008 Edition of NFPA 1851 (effective June 24, 2007) shall be implemented as follows:]~~

~~[(1) — with respect to Section 10.1.2, structural fire fighting ensembles and ensemble elements shall be retired in accordance with Section 10.2.1 of the 2008 Edition of NFPA 1851, no more than 12 years from the date the ensembles or ensemble elements were manufactured, or no more than 10 years from the date the ensemble or ensemble elements were first put into service;]~~

~~[(2) — with respect to Section 10.1.3, proximity fire fighting ensembles and ensemble elements shall be retired in accordance with Section 10.2.1 of the 2008 Edition of NFPA 1851, no more than 12 years from the date the ensembles or ensemble elements were manufactured, or no more than ten years from the date the ensemble or ensemble elements were first put into service; and]~~

~~[(3) — with respect to Section 10.1.3.1, the radiant reflective outer shells shall be retired in accordance with Section 10.2.1 of the 2008 Edition of NFPA 1851, no more than 7 years from the date the outer shells are manufactured or no more than 5 years from the date the outer shells were first put into service.]~~

~~[(e) — Subsections (d) and (e) of this section will expire March 1, 2011.]~~

### **§435.3. Self-Contained Breathing Apparatus.**

The employing entity shall:

- (1) purchase, provide, and maintain a complete self-contained breathing apparatus for each on-duty fire protection personnel who engage in operations where IDLH atmospheres may be encountered, where the atmosphere is unknown or would be exposed to hazardous atmospheres from fire or other emergencies or where the potential for such exposure exists;
- (2) ensure that all self-contained breathing apparatus used by fire protection personnel complies with the minimum standards of the National Fire Protection Association identified in NFPA 1981, Standard on Open-Circuit Self-Contained Breathing Apparatus for Fire Fighters.
  - (A) the National Fire Protection Association standard applicable to a self-contained breathing apparatus is the standard in effect at the time the entity contracts for new, rebuilt, or used self-contained breathing apparatus;
  - (B) an entity may continue to use a self-contained breathing apparatus in use or contracted for before a change in the National Fire Protection Association standard, unless the Commission determines that the continued use of the self-contained breathing apparatus constitutes an undue risk to the wearer, in which case the Commission shall order that the use be discontinued and shall set an appropriate date for compliance with the revised standard;
- (3) develop an air quality program that complies with the most recent edition of the NFPA 1989 Standard on Breathing Air Quality for Emergency Services Respiratory Protection;
- (4) maintain and supply upon request by the Commission, records and reports documenting compliance with Commission requirements concerning self-contained breathing apparatus and breathing air. Records of all tests shall be made and the records shall be retained for a period of no less than three years;
- (5) maintain and provide upon request by the Commission, a departmental standard operating procedure regarding the use of self-contained breathing apparatus; and
- (6) maintain and provide upon request by the Commission, a department standard operating procedure regarding the selection, care, and maintenance of self-contained breathing apparatus that complies with the most recent edition of the NFPA 1852 Standard on Selection, Care, and Maintenance of Open-Circuit Self-Contained Breathing Apparatus (SCBA).

### **§435.5. Commission Recommendations.**

The commission recommends that all employing entities use as a guide the following publications:

- (1) NFPA 1403 "Live Fire Training Evolutions";
- (2) NFPA 1500 "Fire Department Occupational Safety and Health Program;"
- (3) IAFF/IAFC - "Fire Service Joint Labor Management Wellness-Fitness Initiative."

### **§435.7. Fire Department Staffing Studies.**

- (a) Section 419.022(a)(4) Texas Government Code provides that the commission may "on request, assist in performing staffing studies of fire departments." Staffing studies must take into consideration all the objectives and missions of the fire department. The commission does not have the resources or the staff to directly assist in performing the necessary tasks to perform a staffing study. Many staffing studies have been developed that can be used to assist in evaluating the needs of a fire department.
- (b) A city should ultimately decide on the level of fire protection it is willing to provide to its citizens. The city and fire department should, as a minimum, address the needs of prevention, investigation and suppression as

outlined in the appropriate NFPA Standards. That decision should be based on facts, the safety of its citizens, and the safety of the fire fighters providing that protection.

(c) The commission will assist by maintaining information pertinent to fire department staffing. The information shall be maintained in the Ernest A. Emerson Fire Protection Resource Library at the Texas Commission on Fire Protection. Copies shall be made available, free of charge, to anyone requesting such information to the extent permitted by copyright laws.

#### **§435.9. Personal Alert Safety System (PASS).**

The employing entity shall:

(1) purchase, provide, and maintain a PASS device for each on duty fire protection personnel who engage in operations where IDLH atmospheres may be encountered, or where the atmosphere is unknown, or where hazardous conditions from fire or other emergencies exist, or where the potential for such exposure exists;

(2) ensure that all PASS devices used by fire protection personnel comply with the minimum standards of the National Fire Protection Association identified in NFPA 1982, Standard on Personal Alert Safety Systems (PASS) for Fire Fighters:

(A) the National Fire Protection Association standard applicable to a PASS device is the standard in effect at the time the entity contracts for new, rebuilt, or used PASS devices;

(B) an entity may continue to use a PASS device that meets the requirements of an earlier edition of NFPA 1982, unless the commission determines that the continued use of the PASS device constitutes an undue risk to the wearer, in which case the commission shall order that the use be discontinued and shall set an appropriate date for compliance with the revised standard;

(3) ensure that the PASS device assigned to an individual user be inspected at the beginning of each duty period and before each use.

(4) maintain and provide upon request by the commission, a departmental standard operating procedure regarding the proper use, selection, care and maintenance of PASS devices.

#### **§435.11. Incident Management System (IMS)**

(a) The fire department shall develop, maintain and use an incident management system.

(b) The incident management system shall:

(1) include a written operating procedure for the management of emergency incidents;

(2) require that the IMS be used at all emergency incidents;

(3) require operations to be conducted in a manner that recognizes hazards and assists in the prevention of accidents and injuries;

(4) require that all fire protection personnel be trained in the use of the IMS; and

(5) require that the IMS be applied to all drills, exercises and all other situations that involve hazards similar to those encountered at an actual emergency.

(c) The IMS shall meet the requirements of the applicable sections of the National Fire Protection Association 1561, Standard on Fire Department Incident Management System.

(d) The Commission recommends departments follow the National Incident Management System (NIMS) when developing their incident management system.

### **§435.13. Personnel Accountability System.**

(a) The fire department shall develop, maintain and use a personnel accountability system that provides for a rapid accounting of all personnel at an emergency incident.

(b) The accountability system shall:

(1) require all fire protection personnel be trained in the use of the accountability system;

(2) require that the fire protection personnel accountability system be used at all incidents;

(3) require that all fire protection personnel operating at an emergency incident to actively participate in the personnel accountability system; and

(4) require that the incident commander be responsible for the overall personnel accountability system for the incident.

(c) The fire department shall be responsible for developing the system components required to make the personnel accountability system effective.

(d) The personnel accountability system shall meet the minimum standards required by the National Fire Protection Association 1561, Standard on Fire Department Incident Management System. If the standard is revised, the fire department shall have one (1) year from the effective date of the new standard to comply.

### **§435.15. Operating At Emergency Incidents.**

(a) The fire department shall develop, maintain and use a standard operating procedure for fire protection personnel operating at emergency incidents.

(b) The standard operating procedure shall:

(1) specify an adequate number of personnel to safely conduct emergency scene operations;

(2) limit operations to those that can be safely performed by personnel at the scene;

(3) require all personnel to be trained in and use the standard operating procedures; and

(4) comply with §435.17 (Procedures for Interior Structural Fire Fighting).

(c) The fire department may use standards established by the National Fire Protection Association for fire protection personnel operating at an emergency incident.

### **§435.17. Procedures for Interior Structural Fire Fighting (2-In/2-Out Rule).**

(a) The fire department shall develop written procedures that comply with the Occupational Safety and Health Administration's Final Rule, 29 CFR Section 1910.134(g)(4) by requiring:

(1) a team of at least four fire protection personnel must be assembled before an interior fire attack can be made when the fire has progressed beyond the incipient stage;

(2) at least two fire protection personnel to enter the IDLH atmosphere and remain in visual or voice (not radio) contact with each other;

(A) Visual means that the fire protection personnel must be close enough to see each other.

(B) Voice means that the fire protection personnel of the entry team must be close enough to speak to one another without the use of radios.

(3) at least two fire protection personnel remain located outside the IDLH atmosphere to perform rescue of the fire protection personnel inside the IDLH atmosphere;

(4) all fire protection personnel engaged in interior structural fire fighting use self-contained breathing apparatus and be clothed in a complete set of protective clothing as identified in Chapter 435;

(5) all fire protection personnel located outside the IDLH atmosphere be equipped with appropriate retrieval equipment where retrieval equipment would contribute to the rescue of the fire protection personnel that have entered the IDLH atmosphere;

(6) one of the outside fire protection personnel must actively monitor the status of the inside fire protection personnel and not be assigned other duties. The second outside fire protection personnel may be assigned to an additional role, including, but not limited to, incident commander, safety officer, driver-operator, command technician or aide, or fire fighter/EMS personnel, so long as this individual is able to perform assistance or rescue activities without jeopardizing the safety or health of any fire protection personnel working at the scene;

(7) the fire protection personnel outside the IDLH atmosphere must remain in communication (including, but not limited to, radio) with the fire protection personnel in the IDLH atmosphere. Use of a signal line (rope) as a communications instrument for interior fire fighting is not permitted by the commission. This does not preclude the use of rescue guide ropes (guide line or lifeline or by what ever name they may be called) used during structural searches; and

(8) each outside fire protection personnel must have a complete set of protective clothing and self-contained breathing apparatus, as identified in Chapter 435, immediately accessible for use if the need for rescue activities inside the IDLH atmosphere is necessary.

(b) The fire department shall comply with the 2-in/2-out rule as described in this section except in an imminent life-threatening situation when immediate action could prevent the loss of life or serious injury before the team of four fire protection personnel are assembled.

#### **§435.19. Enforcement of Commission Rules.**

(a) The Commission shall enforce all Commission rules at any time, including, but not limited to, Commission investigations, fire department inspections, or upon receiving a written complaint from an identified person or entity of an alleged infraction of a Commission rule.

(b) The Commission shall not provide prior notification of an inspection to a fire department.

(c) Upon receipt of a signed complaint alleging a violation of a Commission rule, the Commission shall have 30 days to initiate an investigation and report back to the complainant its progress.

- (d) Upon substantiating the validity of a written complaint, the Commission shall follow the procedures outlined in Government Code, Chapter 419, §419.011(b) and (c).

#### **§435.21. Fire Service Joint Labor Management Wellness-Fitness Initiative.**

- (a) A fire department shall assess the wellness and fitness needs of the personnel in the department. The procedure used to make this assessment shall be written and made available for commission inspection.
- (b) A fire department shall develop and maintain a standard operating procedure to address those needs.
- (c) The approach to the fitness needs of the department shall be based on the local assessment and local resources.
- (d) The standard operating procedure shall be made available to the commission for inspection.

#### **§435.23. Fire Fighter Injuries.**

- (a) A fire department shall report all Texas Workers' Compensation Commission reportable injuries that occur to on-duty regulated fire protection personnel on the Commission form.
- (b) Minor injuries are those injuries that do not result in the fire fighter missing more than one duty period or does not involve the failure of personal protective equipment. Minor injuries shall be reported within 30 business days of the injury event.
- (c) Major injuries are those that require the fire fighter to miss more than one duty period. Major injuries shall be reported within five business days of the injury event.
- (d) Investigatable injuries are those resulting from the malfunction of personal protective equipment, failure of personal protective equipment to protect the fire fighter from injury, or injuries sustained from failure to comply with any provision of Commission mandated department SOPs. Investigatable injuries shall be reported within five business days of the injury event.
- (e) The regulated entity shall secure any personal protective equipment involved in a fire fighter injury and shall be made available to the Commission for inspection.

#### **§435.25. Courage to be Safe So Everyone Goes Home Program.**

- (a) In an effort to improve firefighter safety in the State of Texas, all regulated entities will ensure that the National Fallen Firefighters Foundation's "Courage to be Safe So Everyone Goes Home" program be completed as part of the continuing education required for certified fire protection personnel by December 1, 2015. Individuals will be credited with four hours of continuing education credit for completing this program.
- (b) All regulated fire protection personnel must complete the National Fallen Firefighters Foundation's "Courage to be Safe So Everyone Goes Home" program prior to December 1, 2015.
- (c) All fire protection personnel appointed after December 1, 2015 will be required to complete the National Fallen Firefighters Foundation's "Courage to be Safe So Everyone Goes Home" program training within one year of appointment to a fire department.
- (d) Departments will report the completion of training through the Commission web based reporting system.
- (e) Failure to complete the National Fallen Firefighters Foundation's "Courage to be Safe So Everyone Goes Home" program before the required deadlines will be considered a violation of continuing education rules found in Chapter 441 of the Commission's Standards Manual.

#### **§435.27. Live Fire Training Structure Evolutions.**

**The most current edition of NFPA 1403, Standard on Live Fire Training Structure Evolutions, shall be used as a guide when developing standard operating procedures for conducting live fire training. The**

following requirements shall apply for all Live Fire Training Structure Evolutions conducted.

- (1) The officer in charge or instructor will ensure that the water supply rate and duration for each individual Live Fire Training Structure Evolution is adequate to control and extinguish the training fire, the supplies necessary for backup lines to protect personnel, and any water needed to protect exposed property.
- (2) The instructor-in-charge shall assign the following personnel:
  - (A) One instructor to each functional crew, which shall not exceed five students.
  - (B) One instructor to each backup line.
  - (C) Additional personnel to backup lines to provide mobility.
  - (D) One additional instructor for each additional functional assignment.
- (3) The officer in charge or instructor will ensure that the buildings or props being utilized for live fire training are in a condition that would not pose an undue safety risk.
- (4) A safety officer shall be appointed for all Live Fire Training Structure Evolutions. The safety officer shall have the authority, regardless of rank, to alter, suspend or control any aspect of the operations when, in his or her judgment, a potential or actual danger, accident, or unsafe condition exists. The safety officer shall not be assigned other duties that interfere with safety responsibilities.
- (5) No person(s) shall play the role of a victim inside the building. .
- (6) Prior to the ignition of any fire, instructors shall ensure that all personal protective clothing and/or self-contained breathing apparatus are NFPA compliant and being worn in the proper manner.
- (7) Prior to conducting any live fire training, a pre-burn briefing session shall be conducted. All participants shall be required to conduct a walk-through of the structure in order to have a knowledge of, and familiarity with, the layout of the building and to be able to facilitate any necessary evacuation of the building.
- (8) A standard operating procedure shall be developed and utilized for Live Fire Training Structure Evolutions. The standard operating procedure shall include, but not be limited to:
  - (A) a Personal Alert Safety System (PASS). A PASS device shall be provided for all participating in live fire training and shall meet the requirements in §435.9 of this title (relating to Personal Alert Safety System (PASS) devices);
  - (B) a Personnel Accountability System that complies with §435.13 of this title shall be utilized;
  - (C) an Incident Management System;
  - (D) use of personal protective clothing and self-contained breathing apparatus;
  - (E) an evacuation signal and procedure; and pre-burn, burn and post-burn procedures.



Need help? Call us at 1.619.525.7286

Welcome. Sign in or Register now. Home | Contact Us | Sign Up for Email | My Account



Your complete resource for fire and safety equipment

FIRE/RESCUE HOME FIRE SAFETY MILITARY INDUSTRIAL THE FIREHOUSE REQUEST A QUOTE ABOUT US CLEARANCE Shopping Cart

Search Check with PayPal Google Checkout Find us on Facebook Español

FIREFIGHTING GEAR & APPAREL

- Boots
Clothing
Coveralls
Eye Protection
Gear Bags
Gloves
Helmets
Hotshield
Proximity Gear
Safety Apparel
Wildland Firefighting Gear

FIREFIGHTING EQUIPMENT

- Adapters
Breathing Apparatus
EMS/First Aid
Fire Dayz Planner
Fire Extinguishers
Fire Extinguisher Accessories
Firefighting Tools
Fire Shelters
Flashlights
Gas Detection
Gifts/Novelty
Hose
Lights and Sirens
Nozzles
Pumps
Rehab
Rescue Equipment
Safety Equipment
Smoke Alarms
Thermo Gel and Foam
Thermal Imaging Cameras
Vehicles

Home » Fire/Rescue » Fire Helmets » Structure Helmets » Cairns 1044 Traditional Composite Fire Helmet



Cairns 1044 Traditional Composite Fire Helmet

Price: \$229.95 Not yet rated. Sign in to review.

Select Options

Color: Black - \$229.95

Quantity:

Add To Shopping Cart

Send to wish list

zoom / larger view

email to friend

PRODUCT DESCRIPTION


The Cairns® 1044 Fire Helmet. Cairns helmets are known for their advanced safety features, features like the high-temperature foam impact cap. Also, this technologically advanced, NFPA-1971-2000-compliant model is outfitted with Cairns' exclusive shell-release system that improves performance and simplifies maintenance.

- Market-leading 5-year shell replacement warranty.
Non-corroding, high-temperature-resistant faceshield/goggle hardware.
Rugged, high-temperature edge will not melt or drip.
Easy front headband adjustment for proper SCBA mask fit.
Simple rear ratchet height adjustment to fit all head sizes.
Headband size (6-3/8 to 8-3/8 fits a wide variety of head sizes.
Durable helmet hanger fits on large hooks and resists bending.
Minimal parts for lower service cost and easier maintenance.
Cairns-exclusive system provides an extra margin of safety - demand it!
Water-based foam for resistance to high heat and flame.
Part of a complete helmet system.
Provides increased thermal and impact protection.
Tube-lock system, instrumental in absorbing the shock of an impact.


CUSTOMERS WHO BOUGHT THIS PRODUCT ALSO LIKED




>> PMI Rope Tech Gloves



>> Amerex ABC Dry Chemical Fire Extinguisher



>> Wildland Fire Fighting Hose Clamp 1 Inch to 1.5 Inch



>> Timberline Wildland Fire Fighting Hose Clamp up to 1 3/4 Inch

RATINGS AND REVIEWS

Be the first to rate this product!

Sign in to rate this product.



Open to the Public
2190 Main Street
San Diego, CA 92113
619-525-7286



Privacy Policy | Shipping & Return Policy | Site Map | Contact Us | Customer Feedback

#7

1040 - CRACKS BACK